PAT-NO: JP02004035387A **DOCUMENT-IDENTIFIER:** JP 2004035387 A

TITLE: ADMIXTURE

PUBN-DATE: February 5, 2004

INVENTOR-INFORMATION:

NAME COUNTRY

ANGELSKAAR, TERJEN/A IWATA, RAITA N/A

ASSIGNEE-INFORMATION:

NAME COUNTRY

MBT HOLDING AGN/A

APPL-NO: JP2002359196 **APPL-DATE:** December 11, 2002

PRIORITY-DATA: 2002200213765 (June 17, 2002)

ABSTRACT:

PROBLEM TO BE SOLVED: To provide an <u>accelerating agent</u> composition having required performance, required stability and required compressive strength and functioning to every type of cement.

SCLUTION: The accelerating agent composition suitable for a cement composition for spraying and composed of a formulation of essential components 1-3, that is a component 1; aluminum sulfate, a component 2; at least one kind of alkanol amine and alkylene diamine and a component 3; hydrofluoric acid, optionally contains at least one kind of components 4-7, that is, a component 4; at least one kind of hydroxide, carbonate and sulfate of sodium, potassium and lithium, a component 5; an aliphatic carboxylic acid, a component 6; amorphous aluminum hydroxide and a component 7; phosphoric acid. Where, at least one kind of the component 4 or the component 5 is existed and

6/16/09. EAST Version: 2.3.0.3

the components are existed in the proportion of 30-60% component 1, 0.1-15% component 2, 0.2-8.0% component 3, $\le 15\%$ component 4, $\le 15\%$ component 5, $\le 15\%$ component 6 and $\le 3\%$ component 7.

COPYRIGHT: (C) 2004, JPO